

Commando 961 CR

FNGINE

Engine Type: Parallel twin with dry sump lubrication.

Displacement: 961cc. **Cooling System:** Air/Oil.

Valve Actuation: Push rod, hydraulic roller lifter, 2-valves per

cylinder.

Bore & Stroke: 88mm x 79mm. Compression Ratio: 10.1:1.

Ignition: Crank fired, electronic fuel injection.

Exhaust: Full stainless steel exhaust system with multiple 3-way

catalytic converter.

TRANSMISSION

Gearbox: Constant mesh 5-speed. Final Drive: 525 O-ring chain. Clutch: Wet multi-plate.

PERFORMANCE

Power: 76.8hp @ 7250rpm. Torque: 81Nm @ 6300rpm.

CHASSIS

Frame: Hand TIG and MIG welded at Norton HQ.

Wheelbase: 1400mm

Rake: 24.5°. Trail: 99mm.

Front Wheel: 36-spoke, 3.5" x 17" polished aluminium rim. Rear Wheel: 40-spoke, 5.0" x 17" polished aluminium rim.

Front Tyre: 120/70/17. Rear Tyre: 180/55/17. Seat Height: 810mm. Tank Size: 15 Litre.

SUSPENSION

Front Suspension: 43mm Ohlins upside-down forks, adjustable

for preload, compression and rebound damping.

Rear Suspension: Ohlins twin shocks with remote reservoir - fully

adjustable.

BODYWORK

Seat Unit: Colour matched seat cowl with optional pillion seat

upgrade.

Mudguard: Carbon fibre.

BRAKES

Front Brakes: Full Brembo system, twin Brembo 320mm floating high carbon steel discs and Brembo 4-piston Mono Bloc radially mounted calipers with ABS, Brembo front brake master cylinder. Rear Brakes: Full Brembo system, Brembo 240mm disc and 2-piston caliper with ABS. Brembo rear brake master cylinder.

ELECTRONICS & CONTROLS

Electronics: 300-watt high-output charging system.

Instruments: Norton analogue speedometer and tachometer.

Lighting: Polished stainless-steel single headlamp.

Steering: Anodised machined billet yokes.

Handlebars: High-grade anodised billet aluminium clip-ons.

COLOUR OPTIONS

Platinum Silver. Matrix Black.

Disclaimer

The products presented are subject to regional applicability and the final specification can change.